

1. PRODUCT AND COMPANY IDENTIFICATION

Product name PolySpec Flex IMO Sealer - Hardener/Side B
Version # 1.0
Revision date 17-Apr-2007
Company information PolySpec
 6614 Gant Road
 Houston, TX 77066 US
Emergency Chemtrec (800) 424-9300
 International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Benzyl Alcohol	100-51-6	< 10
Non-hazardous and other components below reportable levels		> 90
Composition comments	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

3. HAZARDS IDENTIFICATION

Emergency overview Causes skin and eye burns.
Potential short term health effects
Eyes This product causes eye burns. Risk of serious damage to eyes.
Skin Causes skin burns.
Ingestion Do not ingest. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

4. FIRST AID MEASURES

First aid
Eye contact Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention immediately.
Skin contact Get medical attention immediately. Remove and isolate contaminated clothing and shoes. Immediately flush skin with running water for at least 20 minutes. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation Get medical attention immediately. Move to fresh air. Do not use mouth-to-mouth method if victim inhaled the substance. Oxygen or artificial respiration if needed.
Ingestion If material is ingested, immediately contact a physician or poison control center. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth method if victim ingested the substance.
General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Immediate medical attention is required. Keep victim warm. In case of shortness of breath, give oxygen.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media Carbon dioxide (CO2). Alcohol foam. Water spray. Water Fog. Polymer foam. Dry chemical powder.
Fire fighting equipment/instructions Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. Cool containers with flooding quantities of water until well after fire is out.
Specific methods In the event of fire, cool tanks with water spray. Water mist may be used to cool closed containers.
Flash point 200 °F (93.3 °C) Pensky-Martens Closed Cup

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures	Stay upwind. Keep out of low areas. Keep unnecessary personnel away.
Containment procedures	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas. Use water spray to reduce vapors or divert vapor cloud drift.
Personal precautions	Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for cleaning up	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original containers for re-use. Large Spills: Wet down with water and dike for later disposal. After removal flush contaminated area thoroughly with water.

7. HANDLING AND STORAGE

Handling	Do not get this material in your eyes, on your skin, or on your clothing. Do not handle or store near an open flame, heat or other sources of ignition. Surfaces may become slippery after spillage.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment	
Respiratory protection	A NIOSH- approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. In case of insufficient ventilation wear suitable respiratory equipment.
Hand protection	Protective gloves.
Eye protection	Wear chemical goggles. Face-shield.
Skin and body protection	Wear chemical protective equipment that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Wear appropriate chemical resistant gloves. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Wear suitable protective clothing.
General	Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Avoid contact with the skin and the eyes.
Hygiene measures	Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with the skin and the eyes. When using do not smoke.

9. PHYSICAL & CHEMICAL PROPERTIES

Density	8.5005 lb/gal
Form	Liquid.
Specific gravity	1.02

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability	Stable at normal conditions.
Conditions to avoid	Direct sources of heat.
Hazardous polymerization	Will not occur.
Incompatibility	Acids. Alcohols. Amines. Caustics. Cresol. Glycol. Isocyanates. Phenol. Strong oxidizing agents. Vinyl acetates. Will form explosive mixtures in air.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Causes burns.		
Component analysis - LD50			
NIOSH - Selected LD50s and LC50s			
Benzyl Alcohol	100-51-6	Oral LD50 Rat: 1230 mg/kg; Oral LD50 Mouse: 1360 mg/kg; Dermal LD50 Rabbit: 2 g/kg	

12. ECOLOGICAL INFORMATION

Ecotoxicity Components of this product have been identified as having potential environmental concerns.

Environmental effects

Ecotoxicity - Freshwater Fish Species Data

Benzyl Alcohol 100-51-6 96 Hr LC50 fathead minnow: 460 mg/L (Static); 96 Hr LC50 bluegill: 10 mg/L (Static)

Ecotoxicity - Microtox Data

Benzyl Alcohol 100-51-6 5 Min EC50 Photobacterium phosphoreum: 63.7 mg/L; 15 min EC50 Photobacterium phosphoreum: 63.7 mg/L; 30 min EC50 Photobacterium phosphoreum: 71.4 mg/L

Ecotoxicity - Water Flea Data

Benzyl Alcohol 100-51-6 48 Hr EC50 water flea: 23 mg/L

13. DISPOSAL CONSIDERATIONS


Disposal instructions

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. TRANSPORTATION INFORMATION


Department of Transportation (DOT) Requirements

Proper shipping name	PAINT
Hazard class	8
Special provisions	B52, IB3, T4, TP1
Packaging exceptions	154
Packaging non bulk	173
Packaging bulk	241
Quantity limits passenger	5 L
Quantity limits cargo	60 L
Vessel stowage location	A
UN number	UN3066
Packaging group	III
Labels required	8
ERG number	153




International Air Transport Association (IATA) Requirements

Proper shipping name	PAINT RELATED MATERIAL CORROSIVE
Hazard class	8
Special provisions	B52, IB3, T4, TP1
Packaging exceptions	154
Packaging non bulk	173
Packaging bulk	241
Quantity limits passenger	5 L
Quantity limits cargo	60 L
Vessel stowage location	A
UN number	UN3066
Packaging group	III
Labels required	8
Passenger Cargo Pkg Inst	Y818
LQ	818
Packaging Instructions	820
Pkg Inst Cargo Only	



International Maritime Dangerous Goods (IMDG) Code Requirements

Proper shipping name	PAINT
Hazard class	8
Special provisions	163,
Packaging exceptions	154
Packaging non bulk	173
Packaging bulk	241
Quantity limits passenger	5 L
Quantity limits cargo	60 L
Vessel stowage location	A
Item	C9
UN number	UN3066
Packaging group	III
Labels required	8
Hazard ID	80
Transport Category	3



15. REGULATORY INFORMATION

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (superfund) reportable quantity

None

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

NFPA ratings

Health: 3
Flammability: 1
Instability: 0

International regulations

Canada - WHMIS - Ingredient Disclosure List

Benzyl Alcohol 100-51-6 1 % (English Item 169, French Item 170)

State regulations

Massachusetts - Right To Know List

Benzyl Alcohol 100-51-6 Present

Pennsylvania - RTK (Right to Know) List

Benzyl Alcohol 100-51-6 Present

16. OTHER INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Issue date

17-Apr-2007

MSDS sections updated

Exposure Controls / Personal Protection: Respiratory protection
Chemical Stability & Reactivity Information: Incompatibility