

1. PRODUCT AND COMPANY IDENTIFICATION

Product name PolySpec IMO UltraLite TG/TG Bond/TG Primer - Resin/Side A
Version # 1.0
Revision date 17-Jun-2009
Company information PolySpec
 6614 Gant Road
 Houston, TX 77066 US
Emergency Chemtrec (800) 424-9300
 International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Bisphenol-A-(Epichlorohydrin) polymer	25068-38-6	< 60
Aluminum oxide	1344-28-1	< 20
Iron oxide	1309-37-1	< 2.5
Non-hazardous and other components below reportable levels		> 20
Composition comments	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

3. HAZARDS IDENTIFICATION

Emergency overview May cause sensitization by skin contact. Irritating to skin. Harmful in contact with eyes. Danger of serious damage to health by prolonged exposure. May cause breathing disorders and lung damage.

Potential short term health effects

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.
Skin Components of the product may be absorbed into the body through the skin. Irritating to skin. May cause sensitization by skin contact.
Inhalation May cause breathing disorders and lung damage.
Ingestion Do not ingest.
Target organs Eyes. Respiratory system. Skin.

4. FIRST AID MEASURES

First aid

Eye contact Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention if irritation develops or persists.
Skin contact Remove and isolate contaminated clothing and shoes. Wash off immediately with plenty of water. If skin irritation persists, call a physician. Immediately flush skin with running water for at least 20 minutes.
Inhalation If breathing is difficult, give oxygen. Move to fresh air. Get medical attention, if needed.
Ingestion Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Drink plenty of water. Do not induce vomiting without medical advice.
Notes to physician Symptoms may be delayed.
General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off contaminated clothing and shoes immediately.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media Small Fires: Dry chemical, CO2, water spray or regular foam.
 Large Fires: Water spray, fog or regular foam.

Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.
Flash point	600 °F (315.6 °C) Pensky-Martens Closed Cup

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures	Stay upwind. Keep out of low areas. Keep unnecessary personnel away.
Containment procedures	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.
Personal precautions	Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for cleaning up	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original containers for re-use.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes. Do not get this material in contact with skin or eyes. Do not handle or store near an open flame, heat or other sources of ignition. Surfaces may become slippery after spillage.
Storage	Keep in a cool, well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

ACGIH - Threshold Limits Values - Time Weighted Averages (TLV-TWA)

Aluminum oxide	1344-28-1	10 Mg/m ³ TWA (particulate matter containing no asbestos and < 1% crystalline silica)
Iron oxide	1309-37-1	5 Mg/m ³ TWA (dust and fume, as Fe)

ACGIH - Threshold Limits Values - TLV Basis - Critical Effects

Aluminum oxide	1344-28-1	lung; irritation
Iron oxide	1309-37-1	Pneumonconiosis (dust and fume, as Fe)

OSHA - Final PELs - Time Weighted Averages (TWAs)

Aluminum oxide	1344-28-1	15 Mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Iron oxide	1309-37-1	10 Mg/m ³ TWA

Personal protective equipment

Respiratory protection A NIOSH- approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. In case of insufficient ventilation wear suitable respiratory equipment.

Hand protection Protective gloves.

Eye protection Wear chemical goggles. Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves. Wear suitable protective clothing.

General Avoid contact with the skin and the eyes.

Engineering measures to reduce exposure Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Hygiene measures Avoid contact with the skin and the eyes. Handle in accordance with good industrial hygiene and safety practice. When using do not smoke.

9. PHYSICAL & CHEMICAL PROPERTIES

Density	13.7684 lb/gal
Form	Liquid.
Specific gravity	1.6523

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability Stable at normal conditions.

Conditions to avoid Direct sources of heat.
Incompatibility None known.

11. TOXICOLOGICAL INFORMATION

Local effects Risk of serious damage to eyes. Components of the product may be absorbed into the body through the skin. Irritating to skin. May cause sensitization by skin contact.
Sensitization May cause sensitization by skin contact.
Carcinogenicity
ACGIH - Threshold Limits Values - Carcinogens
Aluminum oxide 1344-28-1 A4 - Not Classifiable as a Human Carcinogen
Iron oxide 1309-37-1 A4 - Not Classifiable as a Human Carcinogen (dust and fume, as Fe)
Chronic toxicity Prolonged or repeated exposure may cause lung injury.
Routes of exposure Skin contact.

12. ECOLOGICAL INFORMATION

Ecotoxicity Components of this product have been identified as having potential environmental concerns.

13. DISPOSAL CONSIDERATIONS

Disposal instructions Dispose in accordance with all applicable regulations. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

14. TRANSPORTATION INFORMATION

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

International Air Transport Association (IATA) Requirements

Not regulated as dangerous goods.

International Maritime Dangerous Goods (IMDG) Code Requirements

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

US federal regulations

CERCLA/SARA - Section 313 - Emission Reporting

Aluminum oxide 1344-28-1 1.0 % de minimis concentration (fibrous form only)

Inventory - European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

Aluminum oxide 1344-28-1 215-691-6

Iron oxide 1309-37-1 215-168-2

Inventory - United States - Section 8(b) Inventory (TSCA)

Aluminum oxide 1344-28-1 Present

Iron oxide 1309-37-1 Present

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 Yes
hazardous chemical

CERCLA (superfund) reportable quantity

None

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely No
hazardous substance

Section 311 hazardous Yes
chemical

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

NFPA ratings

Health: 2
Flammability: 1
Instability: 0

International regulations**Canada - 2004 NPRI (National Pollutant Release Inventory)**

Aluminum oxide 1344-28-1 Part 1, Group 1 Substance (fibrous form)

Canada - WHMIS - Ingredient Disclosure List

Aluminum oxide 1344-28-1 1 % (English Item 44, French Item 195)
Iron oxide 1309-37-1 1 % (English Item 762, French Item 1327)

State regulations**Massachusetts - Right To Know List**

Aluminum oxide 1344-28-1 Present
Iron oxide 1309-37-1 Present

New Jersey - Right to Know Hazardous Substance List

Aluminum oxide 1344-28-1 sn 2891
Iron oxide 1309-37-1 sn 1036

Pennsylvania - RTK (Right to Know) List

Aluminum oxide 1344-28-1 Environmental hazard
Iron oxide 1309-37-1 Present

16. OTHER INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Issue date

17-Jun-2009