

1. PRODUCT AND COMPANY IDENTIFICATION

Product name	NovoRez 360+ Solvent Resistant Coating - Hardener/Side B
Version #	2.0
Revision date	05-Jan-2010
Company information	PolySpec 6614 Gant Road Houston, TX 77066 US
Emergency	Chemtrec (800) 424-9300 International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
M-Xylene-.alpha., .alpha.-diamine	1477-55-0	< 60
Non-hazardous and other components below reportable levels		> 40
Composition comments	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

3. HAZARDS IDENTIFICATION

Emergency overview	Kidney injury may occur. Danger of serious damage to health by prolonged exposure. May cause breathing disorders and lung damage. May cause liver damage. Causes skin and eye burns.
Potential short term health effects	
Eyes	This product causes eye burns. Risk of serious damage to eyes.
Skin	Causes skin burns.
Inhalation	May cause breathing disorders and lung damage.
Ingestion	Do not ingest. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.
Target organs	Eyes. Kidney. Liver. Respiratory system. Skin.
Main symptoms	Liver injury may occur. Kidney injury may occur.

4. FIRST AID MEASURES

First aid	
Eye contact	Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention immediately.
Skin contact	Get medical attention immediately. Remove and isolate contaminated clothing and shoes. Immediately flush skin with running water for at least 20 minutes. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation	Get medical attention immediately. Move to fresh air. Do not use mouth-to-mouth method if victim inhaled the substance. Oxygen or artificial respiration if needed. If breathing is difficult, give oxygen. Get medical attention, if needed.
Ingestion	If material is ingested, immediately contact a physician or poison control center. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not use mouth-to-mouth method if victim ingested the substance.
Notes to physician	Symptoms may be delayed.
General advice	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Immediate medical attention is required. Keep victim warm. In case of shortness of breath, give oxygen.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media	Small Fires: Dry chemical, CO2, water spray or regular foam. Large Fires: Water spray, fog or regular foam.
-------------------------------------	--

Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.
Flash point	212 °F (100 °C)

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures	Stay upwind. Keep out of low areas. Keep unnecessary personnel away.
Containment procedures	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.
Personal precautions	Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for cleaning up	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original containers for re-use.

7. HANDLING AND STORAGE

Handling	Do not get this material in your eyes, on your skin, or on your clothing. Do not handle or store near an open flame, heat or other sources of ignition. Surfaces may become slippery after spillage.
Storage	Keep out of the reach of children. Keep in a cool, well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

ACGIH - Threshold Limits Values - Ceilings (TLV-C)

M-Xylene-.alpha., .alpha.-diamine 1477-55-0 0.1 Mg/m3 Ceiling

ACGIH - Threshold Limits Values - TLV Basis - Critical Effects

M-Xylene-.alpha., .alpha.-diamine 1477-55-0 irritation; blood

Personal protective equipment

Respiratory protection	A NIOSH- approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. In case of insufficient ventilation wear suitable respiratory equipment.
Hand protection	Protective gloves.
Eye protection	Wear chemical goggles. Face-shield.
Skin and body protection	Wear chemical protective equipment that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Wear appropriate chemical resistant gloves. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Wear suitable protective clothing.
General	Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Avoid contact with the skin and the eyes.

Hygiene measures	Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with the skin and the eyes. When using do not smoke.
-------------------------	--

9. PHYSICAL & CHEMICAL PROPERTIES

Boiling point	482 °F (250 °C)
Density	9.2963 lb/gal
Form	Liquid.
Specific gravity	1.116

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability	Stable at normal conditions.
Conditions to avoid	Direct sources of heat.
Hazardous polymerization	Will not occur.
Incompatibility	None known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Causes burns.
Local effects	Liver toxicity.
Component analysis - LD50	
NIOSH - Selected LD50s and LC50s	
M-Xylene-.alpha., .alpha.-diamine 1477-55-0	Inhalation LC50 Rat: 700 ppm/1H; Oral LD50 Rat: 930 mg/kg; Dermal LD50 Rabbit: 2 g/kg
Chronic toxicity	Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury.
Subchronic toxicity	Kidney injury may occur.
Further information	Symptoms may be delayed.

12. ECOLOGICAL INFORMATION

Ecotoxicity	This material is not expected to be harmful to aquatic life.
--------------------	--


13. DISPOSAL CONSIDERATIONS

Disposal instructions	This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.
------------------------------	--

14. TRANSPORTATION INFORMATION


Department of Transportation (DOT) Requirements

Proper shipping name	PAINT
Hazard class	8
Special provisions	B2, IB2, T7, TP2
Packaging exceptions	154
Packaging non bulk	173
Packaging bulk	242
Quantity limits passenger	1 L
Quantity limits cargo	30 L
Vessel stowage location	A
UN number	UN3066
Packaging group	II
Labels required	8
ERG number	153




International Air Transport Association (IATA) Requirements

Proper shipping name	PAINT RELATED MATERIAL CORROSIVE
Hazard class	8
Special provisions	B2, IB2, T7, TP2
Packaging exceptions	154
Packaging non bulk	173
Packaging bulk	242
Quantity limits passenger	1 L
Quantity limits cargo	30 L
Vessel stowage location	A
UN number	UN3066
Packaging group	II
Labels required	8
Passenger Cargo Pkg Inst	Y808
LQ	808
Packaging Instructions	812
Pkg Inst Cargo Only	



International Maritime Dangerous Goods (IMDG) Code Requirements

Proper shipping name	PAINT
Hazard class	8
Special provisions	163,
Packaging exceptions	154
Packaging non bulk	173
Packaging bulk	242
Quantity limits passenger	1 L
Quantity limits cargo	30 L
Vessel stowage location	A
Item	C9
UN number	UN3066
Packaging group	II
Labels required	8
Hazard ID	80
Transport Category	2



15. REGULATORY INFORMATION

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Inventory - European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

M-Xylene-.alpha.,.alpha.-diamine 1477-55-0 216-032-5

Inventory - United States - Section 8(b) Inventory (TSCA)

M-Xylene-.alpha.,.alpha.-diamine 1477-55-0 Present

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 Yes
hazardous chemical

CERCLA (superfund) reportable quantity

None

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

NFPA ratings

Health: 3
Flammability: 1
Instability: 0

International regulations

Canada - WHMIS - Ingredient Disclosure List

M-Xylene-.alpha.,.alpha.-diamine 1477-55-0 1 % (English Item 1697, French Item 1725)

State regulations

Massachusetts - Right To Know List

M-Xylene-.alpha.,.alpha.-diamine 1477-55-0 Present

New Jersey - Right to Know Hazardous Substance List

M-Xylene-.alpha.,.alpha.-diamine 1477-55-0 sn 1320

Pennsylvania - RTK (Right to Know) List

M-Xylene-.alpha.,.alpha.-diamine 1477-55-0 Present

16. OTHER INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Issue date

05-Jan-2010