

1. PRODUCT AND COMPANY IDENTIFICATION

Product name PolySpec Stripe - Resin/Side A
Version # 1.0
Revision date 23-Sep-2009
Company information PolySpec
 6614 Gant Road
 Houston, TX 77066 US
Emergency Chemtrec (800) 424-9300
 International (703) 527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
P-Chloro-a,a,a-trifluorotoluene	98-56-6	< 40
Propylene glycol monomethyl ether acetate	108-65-6	< 40
Non-hazardous and other components below reportable levels		> 40
Composition comments	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

3. HAZARDS IDENTIFICATION

Emergency overview Health injuries are not known or expected under normal use. May be ignited by heat, sparks or flames. Flammable/Combustible Material.

Potential short term health effects

- Eyes** Contact with eyes may cause irritation.
- Skin** Not expected to be a primary skin irritant.
- Inhalation** May cause irritation of respiratory tract.
- Ingestion** Do not ingest. May be harmful if swallowed.

4. FIRST AID MEASURES

First aid

- Eye contact** Flush eyes with water as a precaution. If irritation persists get medical attention.
- Skin contact** Rinse with water. Get medical attention if irritation develops or persists.
- Inhalation** Call a physician if symptoms develop or persist. If breathing is difficult, give oxygen.
- Ingestion** Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large amount does occur, seek medical attention.

General advice If you feel unwell, seek medical advice (show the label where possible).

5. FIRE FIGHTING MEASURES

Unusual fire & explosion hazards Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard. Containers may explode when heated.

Suitable extinguishing media Carbon dioxide (CO₂). Alcohol foam. Water spray. Polymer foam. Dry chemical powder.

Fire fighting equipment/instructions Move containers from fire area if you can do it without risk. In the event of fire, wear self contained breathing apparatus. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. ALWAYS stay away from tanks engulfed in flame. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Cool containers with flooding quantities of water until well after fire is out.

Specific methods In the event of fire, cool tanks with water spray. Water mist may be used to cool closed containers.

Flash point 114 °F (45.6 °C) Pensky-Martens Closed Cup

6. ACCIDENTAL RELEASE MEASURES

Evacuation procedures	Keep unnecessary personnel away. Ventilate closed spaces before entering. Stay upwind. Keep out of low areas.
Containment procedures	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas. Use water spray to reduce vapors or divert vapor cloud drift.
Personal precautions	Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.
Methods for cleaning up	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original containers for re-use. Should not be released into the environment. Large Spills: Wet down with water and dike for later disposal. After removal flush contaminated area thoroughly with water.

7. HANDLING AND STORAGE

Handling	Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe gas/fumes/vapor/spray. All equipment used when handling the product must be grounded. Handle and open container with care. Surfaces may become slippery after spillage.
Storage	Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. The pressure in sealed containers can increase under the influence of heat. Use care in handling/storage. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protective equipment	
Respiratory protection	No personal respiratory protective equipment normally required.
Eye protection	Avoid contact with eyes.
Skin and body protection	Wear suitable protective clothing.
General	Structural firefighters protective clothing will only provide limited protection. Wear suitable protective equipment.
Engineering measures to reduce exposure	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Hygiene measures	When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL & CHEMICAL PROPERTIES

Density	9.2704 lb/gal
Form	Liquid.
Specific gravity	1.1124

10. CHEMICAL STABILITY & REACTIVITY INFORMATION

Stability	Risk of ignition.
Conditions to avoid	High temperatures. Direct sources of heat.
Hazardous polymerization	Will not occur.
Incompatibility	Strong acids. Will form explosive mixtures in air. This product is incompatible with nitrates.

11. TOXICOLOGICAL INFORMATION

Component analysis - LD50

NIOSH - Selected LD50s and LC50s

P-Chloro-a,a,a-trifluorotoluene	98-56-6	Oral LD50 Rat: 13 g/kg; Oral LD50 Mouse: 11500 mg/kg
Propylene glycol monomethyl ether acetate	108-65-6	Oral LD50 Rat: 8532 mg/kg; Dermal LD50 Rabbit: >5 g/kg

Further information	This product has no known adverse effect on human health.
----------------------------	---

12. ECOLOGICAL INFORMATION

Ecotoxicity Components of this product are hazardous to aquatic life.

Environmental effects Harmful to aquatic life.

Ecotoxicity - Microtox Data

P-Chloro-a,a,a-trifluorotoluene 98-56-6 5 Min EC50 Photobacterium phosphoreum: 11.1 mg/L; 15 min EC50 Photobacterium phosphoreum: 13.4 mg/L; 30 min EC50 Photobacterium phosphoreum: 14.3 mg/L

13. DISPOSAL CONSIDERATIONS

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructions Dispose in accordance with all applicable regulations. If discarded, this product is considered a RCRA ignitable waste, D001. Incinerate the material under controlled conditions in an approved incinerator. Dispose of this material and its container at hazardous or special waste collection point. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

14. TRANSPORTATION INFORMATION

Department of Transportation (DOT) Requirements

Proper shipping name	PAINT RELATED MATERIAL
Hazard class	3
Special provisions	B1, B52, IB3, T2, TP1
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
Quantity limits passenger	60 L
Quantity limits cargo	220 L
Vessel stowage location	A
UN number	UN1263
Packaging group	III
Labels required	3
ERG number	128

DOT



International Air Transport Association (IATA) Requirements

Proper shipping name	PAINT RELATED MATERIAL
Hazard class	3
Special provisions	B1, B52, IB3, T2, TP1
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
Quantity limits passenger	60 L
Quantity limits cargo	220 L
Vessel stowage location	A
UN number	UN1263
Packaging group	III
Labels required	3
Passenger Cargo Pkg Inst	Y309
LQ	309
Packaging Instructions	310
Pkg Inst Cargo Only	

IATA



International Maritime Dangerous Goods (IMDG) Code Requirements

Proper shipping name	PAINT
Hazard class	3
Special provisions	163, 640E
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
Quantity limits passenger	60 L
Quantity limits cargo	220 L
Vessel stowage location	A
Item	F1
UN number	UN1263
Packaging group	III
Labels required	3
Hazard ID	30
Transport Category	3

IMDG



15. REGULATORY INFORMATION

US federal regulations

Inventory - European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

P-Chloro-a,a,a-trifluorotoluene	98-56-6	202-681-1
Propylene glycol monomethyl ether acetate	108-65-6	203-603-9

Inventory - United States - Section 8(b) Inventory (TSCA)

P-Chloro-a,a,a-trifluorotoluene	98-56-6	Present
Propylene glycol monomethyl ether acetate	108-65-6	P

Occupational safety and health administration (OSHA)

29 CFR 1910.1200 Yes
hazardous chemical

CERCLA (superfund) reportable quantity

None

Superfund amendments and reauthorization act of 1986 (SARA)

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

NFPA ratings

Health: 0
Flammability: 2
Instability: 0

State regulations

Pennsylvania - RTK (Right to Know) List

P-Chloro-a,a,a-trifluorotoluene 98-56-6 environmental hazard

16. OTHER INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Issue date

23-Sep-2009