

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name** TuffRez 205 Epoxy Wall Coating - Resin/Side A  
**Version #** 1.0  
**Revision date** 03-Apr-2007  
**Company information** PolySpec  
 6614 Gant Road  
 Houston, TX 77066 US  
**Emergency** Chemtrec (800) 424-9300  
 International (703) 527-3887

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Diglycidyl ether of Bisphenol-A	25068-38-6	< 80
Non-hazardous and other components below reportable levels		> 10
<b>Composition comments</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	

## 3. HAZARDS IDENTIFICATION

**Emergency overview** Irritating to eyes. May cause sensitization by skin contact. Irritating to skin.  
**Potential short term health effects**  
**Eyes** Causes eye irritation.  
**Skin** Irritating to skin. May cause sensitization by skin contact.  
**Inhalation** May cause irritation of respiratory tract.  
**Ingestion** Do not ingest.

## 4. FIRST AID MEASURES

**First aid**  
**Eye contact** Immediately flush eyes with plenty of water for at least 20 minutes.  
**Skin contact** Remove and isolate contaminated clothing and shoes. If skin irritation persists, call a physician. Wash off immediately with plenty of water. Immediately flush skin with running water for at least 20 minutes.  
**Inhalation** Call a physician if symptoms develop or persist. If breathing is difficult, give oxygen.  
**Ingestion** Drink plenty of water. Do not induce vomiting without medical advice.  
**General advice** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off contaminated clothing and shoes immediately. If you feel unwell, seek medical advice (show the label where possible).

## 5. FIRE FIGHTING MEASURES

**Suitable extinguishing media** Small Fires: Dry chemical, CO2, water spray or regular foam.  
 Large Fires: Water spray, fog or regular foam.  
**Fire fighting equipment/instructions** Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in flame. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.  
**Flash point** 350 °F (176.7 °C) Pensky-Martens Closed Cup

## 6. ACCIDENTAL RELEASE MEASURES

**Evacuation procedures** Stay upwind. Keep out of low areas. Keep unnecessary personnel away.  
**Containment procedures** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.

<b>Personal precautions</b>	Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
<b>Methods for cleaning up</b>	Avoid dust formation. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Never return spills in original containers for re-use.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Wear personal protective equipment. Avoid contact with eyes. Do not get this material in contact with skin or eyes. Do not handle or store near an open flame, heat or other sources of ignition. Surfaces may become slippery after spillage.
<b>Storage</b>	Keep in a cool, well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Do not freeze.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Personal protective equipment</b>	
<b>Respiratory protection</b>	In case of insufficient ventilation wear suitable respiratory equipment. No personal respiratory protective equipment normally required.
<b>Hand protection</b>	Protective gloves.
<b>Eye protection</b>	Wear chemical goggles. Wear face-shield and protective suit for abnormal processing problems.
<b>Skin and body protection</b>	Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves. Wear suitable protective clothing.
<b>General</b>	Avoid contact with the skin and the eyes.
<b>Engineering measures to reduce exposure</b>	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
<b>Hygiene measures</b>	Avoid contact with the skin and the eyes. Handle in accordance with good industrial hygiene and safety practice. When using do not smoke.

## 9. PHYSICAL & CHEMICAL PROPERTIES

<b>Density</b>	10.2828 lb/gal
<b>Form</b>	Liquid.
<b>Specific gravity</b>	1.2346

## 10. CHEMICAL STABILITY & REACTIVITY INFORMATION

<b>Stability</b>	Stable at normal conditions.
<b>Conditions to avoid</b>	Direct sources of heat.
<b>Incompatibility</b>	None known.

## 11. TOXICOLOGICAL INFORMATION

<b>Local effects</b>	Irritating to eyes. Irritating to skin. May cause sensitization by skin contact.
<b>Component analysis - LD50</b>	
<b>NIOSH - Selected LD50s and LC50s</b>	
Diglycidyl ether of Bisphenol-A	25068-38-6 Oral LD50 Rat: 11400 mg/kg; Oral LD50 Mouse: 15600 mg/kg
<b>Sensitization</b>	May cause sensitization by skin contact.
<b>Routes of exposure</b>	Skin contact.

## 12. ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Components of this product have been identified as having potential environmental concerns.
--------------------	---

## 13. DISPOSAL CONSIDERATIONS

<b>Disposal instructions</b>	Dispose in accordance with all applicable regulations. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.
------------------------------	--

